

Adjustable-Angle Thermometer Model AS6



SIMPLE ADJUSTMENT

Just two screws permit case to be rotated 180° and stem to be positioned 10° increments allowing user to select the most desirable viewing position.

EASY READABILITY

Lens front blue liquid filled thermometer tube is mounted on V-shaped aluminum scale with bold black lines and numerals.

ACCURATE

Calibrated against standards traceable to the National Institute of Standards and Technology and guaranteed accurate to ± one scale division.

CONSTRUCTION

Standard with protective slotted bulb guard. Black molded ABS case with glass front to exclude dirt and dust is standard for ranges up to 240°F* (114°C). Aluminum case is optional at additional charge. Plastic face is optional at additional charge. *ABS case should not be subjected to temperatures greater than 200°F*

CONNECTION ASSEMBLY

Swivel nut has 1 1/4" - 18" NEF thread. Comes complete with mounting flange (P/N: All-3I)

See page 3 for case dimensions.



CAT. NO. AS6N-9 ▶

CATALOG NUMBERS

FORM	SCALE SIZE	STEM LENGTHS		
		6"	9"	12"
ADJUST ANGLE	7"	AS6L-7	-	-
	9"	AS6L-9	AS6N-9	AS6Q-9

STANDARD TEMPERATURE RANGES

CODE	FAHRENHEIT	SCALE SIZE		CODE	CELSIUS	SCALE 9" Only	CODE	DUAL SCALE (both °F and °C)	SCALE 9" Only
		7"	9"						
09	-40 to 110°F	2°	2°	CO	-40 to 40°C	1°	DA	-40 to 110°F & -40 to 43°C	2°/1°
16	0 to 120°F	1°	1°	CC	-15 to 50°C	1/2°	DC	0 to 120°F & -17 to 49°C	1°/1/2°
18	0 to 160°F	2°	2°	CD	-15 to 70°C	1°	DD	0 to 160°F & -17 to 71°C	2°/1°
36	20 to 180°F	2°	2°		-	-	DF	20 to 180°F & -6 to 82°C	2°/1°
42	30 to 240°F	2°	2°	CH	0 to 115°C	1°	DH	30 to 240°F & 0 to 114°C	2°/1°

HOW TO ORDER - PLEASE SPECIFY THE FOLLOWING:

MODEL #	STEM LENGTH	SCALE SIZE	RANGE	OPTIONS
AS6	L = 6" stem N = 9" stem Q = 12" stem	7 = 7" scale 9 = 9" scale	2 digit code from tables	AL = Aluminum Case P = Plastic Lens

All Island Industrial Sales
681 Grand Boulevard, Unit 3
Deer Park, New York, 11729

Tel: 1 (866) 415-2002
Fax: 1 (866) 415-3019
Sales@industrial-thermometer.com
<http://www.industrial-thermometer.com>